

DECLARATION OF PERFORMANCE

in accordance with the CPR Regulation (EU) N° 305/2011

1. Unique identification code of the product type:

QUICK-STEP HYDROKIT

2. Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Sealant used for sealing glazing applications.

Sealants used for sanitary applications.

Construction product in accordance with applicable harmonized specifications:

EN 15651-1:2012: Type F - EXT-INT: CLASS 25LM

EN 15651-2:2012: Type G: CLASS 25LM

EN 15651-3:2012: Type S: CLASS XS1

3. Name and contact address of the manufacturer as required pursuant to Article 11(5):

Rectavit NV/SA – Ambachtenlaan 4 – B-9080 Lochristi – Belgium

4. System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3

System 3: for reaction to fire

5. The notified body: **Ginger CEBTP (NB 0074)**, has carried out **Determination of the Product Type under system 3.**

6. Declared performances:

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Elastic recovery	≥ 70%	
Resistance to flow	≤ 3 mm	
Secant modulus at 23°C	≤ 0,4 MPa	
Secant modulus at -20°C	≤ 0,6 MPa	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Loss of volume	≤ 10%	
Resistance to compression	0,26 MPa	
Microbiological growth	0	
Durability	Passe	

*NPD, no performance declared

*NF, no failure

Conditioning, **Methode A**

Substrate: **Aluminium, Mortar, Glass**

7. The performance of this product, identified under §1, is in conformity with the declared performance under §6.

This declaration of performance is issued under the sole responsibility of the manufacturer, identified under §3:

Signed on behalf of the manufacturer by :
Lochristi, May 15, 2014

Bernard Lamote
Technical Services

A handwritten signature in blue ink, appearing to read 'Bernard Lamote'.

CE Marking

in accordance with the CPR Regulation (EU) N° 305/2011



NB 0074

14

Rectavit NV/SA – Ambachtenlaan 4 – B-9080 Lochristi – Belgique

Reference nr of DoP : 230492

EN 15651-1:2012

EN 15651-2:2012

EN 15651-3:2012

Sealant for facade for interior and exterior application.

Sealant used for sealing glazing applications.

Sealants used for sanitary applications.

QUICK-STEP HYDROKIT

EN 15651-1:2012, Type F - EXT-INT: CLASS 25LM

EN 15651-2:2012, Type G: CLASS 25LM

EN 15651-3:2012, Type S: CLASS XS1

Conditioning, Methode A

Substrate: Aluminium, Mortar, Glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Elastic recovery	≥ 70%	
Resistance to flow	≤ 3 mm	
Secant modulus at 23°C	≤ 0,4 MPa	
Secant modulus at -20°C	≤ 0,6 MPa	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Loss of volume	≤ 10%	
Resistance to compression	0,26 MPa	
Microbiological growth	0	
Durability	Passe	